

CO-12 & 15 Series

FEATURES

- TTL/HCMOS Output compatible
- 14 Pin Full Size
- Industry Standard
- Wide Frequency Range
- Low Cost
- Resistance Weld Package
- 3.3V Available

The CO-12 series oscillator is TTL/HCMOS compatible. CO-15 series is with 3.3V power supply voltage. The metal package with pin#7 case ground acts as shielding to minimize EMI radiation.



ELECTRICAL SPECIFICATIONS

Parameter		Condition	CO-12	CO-15
Frequency Range	Fo		0.5MHz~150.00MHz	
Frequency Stability*		All Condition*	±25ppm, ±50ppm, ±100ppm	
Operating Temperature Range	T _{OPR}		0°C ~ 70°C (-40°C ~ +85°C option)	
Storage Temperature Range	T _{STG}		-55°C ~ +125°C	
Power supply Voltage	V _{DD}		5.0V +/- 10%	3.3V +/- 10%
Aging (First Year)		25°C ± 3°C	± 5ppm	
Supply Current	I _{DD}	0.5MHz to 23.999MHz	20mA Max	15mA Max
		24.000MHz to 49.999MHz	30mA Max	20mA Max
		50.000MHz to 69.999MHz	40mA Max	30mA Max
		70.000MHz to 150.000MHz	60mA Max	45mA Max
Output Symmetry	Sym	1/2V _{DD}	40/60% (45/55% Option)	
Rise time	T _r	10% V _{DD} ~ 90% V _{DD}	10 nS Max	8 nS Max
Fall Time	T _f	90% V _{DD} ~ 10% V _{DD}	10 nS Max	8 nS Max
Output Voltage	V _{OH}		90% V _{DD} min	
	V _{OL}		10% V _{DD} max	
Output load	TTL Load		1~10TTL	1~5TTL
	HCMOS Load		~50M:50pF ~70M:30pF ~150M:15pF	~50M:30pF ~150M:15pF
Start-up Time		T _s	10mS Max	

*Include: 25°C tolerance, operating temperature range, input voltage change, aging, load change, shock and vibration

DIMENSIONS

Unit: mm

