



中川電子有限公司  
*Nakagawa Electronics Limited*

VS9: FUNDAMENTAL LVPECL SERIES: HF VCXO, LVPECL, +3.3 VDC

**DESCRIPTION:** A voltage crystal controlled oscillator, high frequency, highly stable oscillator, adhering to Low Voltage Differential Signaling (LVPECL) Standards. The output can be Tri-stated to facilitate testing or combined multiple clocks. The device is contained in a sub-miniature, very low profile, leadless ceramic SMD package with 6 gold contact pads. This miniature oscillator is ideal for today's automated assembly environments.

**APPLICATIONS AND FEATURES:**

- Infiniband; Fiber Channel; SATA; 10GbE; Network Processors; SOHO Routing; SONET/SDH
- Common Frequencies: 38.88 MHz; 77.76MHz; 155.52 MHz; 156.25 MHz; 161.1328 MHz;
- +3.3 VDC LVPECL
- Frequency Range from 1.000 to 180.000 MHz
- No Multiplication is used, low phase noise and jitter
- Miniature Ceramic SMD Package Available on Tape and Reel
- Lead Free and ROHS Compliant

中國 • 香港 • 九龍官塘開源道 55 號 開聯工業中心 7 字樓 A 座 1-2 號  
*Block A, Flat 1-2, 7/F, Hoi Yuen Road, Kwun Tong, Kln, Hong Kong, China*  
Tel: 852-23899201 Fax: 852-23410001 E-mail: info@nkg.com.hk



■ ABSOLUTE MAXIMUM RATINGS:

PARAMETER	SYMBOL	VALUE	UNIT
Operating temperature range	Ta	-40...+85	°C
Storage temperature range	T(stg)	-55...+90	°C
Supply voltage	Vcc	+4.6	VDC
Maximum Input Voltage	Vi	Vss-0.5...Vcc+0.5	VDC
Maximum Output Voltage	Vo	Vss-0.5...Vcc+0.5	VDC

■ ELECTRICAL PARAMETERS:

PARAMETER	SYMBOL	TEST CONDITIONS <sup>*1</sup>	VALUE	UNIT
Nominal Frequency	fo		1 to 180	MHz
Supply Voltage	Vcc		+3.3 ±5%	VDC
Supply Current	Is		100.0 MAX	mA
Output Logic Type			LVPECL	
Load		Connected between each output and Vcc – 2.0 VDC	50	Ω
Output Voltage Levels	Voh Vol	min max	Vcc-1.025 Vcc-1.620	VDC VDC
Duty Cycle	DC	Measured at 50% of output voltage swing	40/60 to 60/40 or 45/55 to 55/45	%
Rise / Fall Time	tr / tf	Measured at 20/80% and 80/20% output voltage swing	0.5 TYP	ns
Frequency Stability		Overall conditions	±50 ** (note 7)	ppm
Jitter	J	Integrated Phase tji RMS, Fj = 12 kHz...20 MHz	0.3 TYP**	ps
		Integrated Phase RMS tii offset frequency 50KHz to 80MHz	0.5 TYP**	ps
		Deterministic period Jitter tdj using wavecrest analyz.	0.0TYP **	ps
		Random period Jitter trj using wavecrest analyz.	2.5 TYP **	ps
		Peak to Peak Jitter Tp-p using wavecrest analyz.	25 TYP**	ps
Phase Noise typ. @155.52MHz	Ɛ(Δf)	Δf=10 Hz	-65	dBc/Hz
	Ɛ(Δf)	Δf=1 KHz	-120	dBc/Hz
	Ɛ(Δf)	Δf=10 KHz	-140	dBc/Hz
	Ɛ(Δf)	Δf= >=100 KHz	-145	dBc/Hz
Control Voltage Range	VC	Positive slope; 10% linearity MAX	0 to +3.3	VDC
Settability	Vfo		+1.65 ± 0.25	VDC
Absolute Pull Range	APR	Minimum guaranteed freq. pull over Δf/fc, over all conditions	See Part Numbering	ppm
Input Impedance	Zin		10 MIN	KΩ
Modulation Bandwidth	BW	-3 dB	10 MIN	KHz
Enable High Option; Pin 2 Output Enabled Output Disabled	En Dis	High Voltage or No Connect Ground	0.7•Vcc MIN 0.3•Vcc MAX	VDC VDC
Enable Low Option; Pin 2 Output Disabled Output Enabled	Dis En	High Voltage Ground or No Connect	0.7•Vcc MIN 0.3•Vcc MAX	VDC VDC

\*1 Test Conditions Unless Stated Otherwise: Nominal Vcc, Nominal Load, +25 ±3°C

\*2 Frequency Dependent

\*3 May not be Available With All Temperature Ranges or Frequencies — Please Consult Factory

\*4 Measured with Wavecrest SIA-3000A 10,000, Cycles no filtering

\*5 Calculated from Agilent 5500 phase noise measurements

\*6 Measured with Agilent 5500

\*7 Tighter stabilities maybe available upon request – please consult factory

中國 • 香港 • 九龍官塘開源道 55 號 開聯工業中心 7 字樓 A 座 1-2 號

Block A, Flat 1-2, 7/F, Hoi Yuen Road, Kwun Tong, Kln, Hong Kong, China

Tel: 852-23899201 Fax: 852-23410001 E-mail: info@nkg.com.hk



中川電子有限公司  
Nakagawa Electronics Limited

■ PART NUMBERING SYSTEM:

SERIES	SYMMETRY	TEMPERATURE RANGE (°C)	ABSOLUTE PULL RANGE	FREQUENCY (MHz)	Enable/Disable
VS9: UHF +3.3Vdc VCXO with LVPECL Comp. Output	A: 40/60 to 60/40% T: 45/55 to 55/45%	R: 0...+50 S: 0...+70 U: -20...+70 V: -40...+85	K: ±20 ppm L: ±25 ppm F: ±32 ppm H: ±50 ppm G: ±80 ppm J: ±100 ppm*(note 3)	1...180.000	Enable High – standard (Omit Suffix) EL; Enable Low

**EXAMPLE: VS9ASH -155.520**

VCXO, 7x5mm Package, +3.3 VDC Supply Voltage, LVPECL Output, Standard Symmetry, 0...+70°C Operating Temperature Range, ±50 ppm APR, 50 ppm stability, 155.520 MHz

■ MECHANICAL PARAMETERS:

**INDICATES PIN 1**

**OUTLINE TOLERANCE:**  
±0.006" / 0.15mm  
(Unless otherwise specified)

**PIN FUNCTIONS:**  
[1] VOLTAGE CONTROL  
[2] ENABLE/ DISABLE, OR NO CONNECT  
[3] CASE GROUND  
[4] OUTPUT  
[5] COMP. OUTPUT  
[6] SUPPLY VOLTAGE


**MARKING:**  
VS9ASH  
155.52  
RAL D/C

\*0.01µF external by-pass filter is recommended as seen on solder pattern.

**SOLDER PATTERN**

中國 • 香港 • 九龍官塘開源道 55 號 開聯工業中心 7 字樓 A 座 1-2 號  
Block A, Flat 1-2, 7/F, Hoi Yuen Road, Kwun Tong, Kln, Hong Kong, China  
Tel: 852-23899201 Fax: 852-23410001 E-mail: info@nkg.com.hk

■ REFLOW PROFILE:



中國 • 香港 • 九龍官塘開源道 55 號 開聯工業中心 7 字樓 A 座 1-2 號  
Block A, Flat 1-2, 7/F, Hoi Yuen Road, Kwun Tong, Kln, Hong Kong, China

Tel: 852-23899201 Fax: 852-23410001 E-mail: info@nkg.com.hk